

FLS Series Flail Mower



BULLY FLS Series Flail Mowers are an ideal light-duty flail mower for hobby farmers with compact and sub-compact tractors, 15 to 30hp.

The gearbox, with incorporated freewheel, produces a high 3000 rpm rotor speed that results in a superior cut on areas of lawn, parkland or smallholding farms.

Front metal deflectors keep debris and other material under the mulcher and away from the tractor and operator. Height adjustable replaceable skid plates and rear roller keep blades out of the dirt, protect the rotor and assist with implement longevity.



Code	TFLS105	TFLS125	TFLS145
Size reference	1.05m 3'6" 41"	1.25m 4'1" 49"	1.45m 4'9" 57"
Side transmission	Belt drive		
Belts	Three (3) SPA type		
Gearbox	30hp, 540rpm with freewheel		
PTO shaft	Series 4		
Skids	Adjustable, three (3) positions		
Rear roller	Ø 102mm, height adjustable		
Finish	Powder coated		
Rotor swing dia. (mm)	280		
Rotor diameter (mm)	76		
Rotor speed (rpm)	3000		
Type of blade	Hammer standard 'Y' blades on request		
No. of blades	18 36	20 40	24 48
Tower position/offset	Fixed/bolt-on with two (2) mounting positions, 100mm apart		
Linkage	Category 1		
Guarding	Standard with CE compliant, individual metal flap guarding		
Overall width (mm)	1230	1430	1630
Working width (mm)	1050	1250	1450
Cutting height (mm)	15 - 45		
Tractor range (hp)	15 - 30	20 - 30	25 - 30
Weight (kg)	158	170	182

Parts

EF100.00.105Y FLS105 'Y' blade kit (36 blades only)
EF100.00.125Y FLS125 'Y' blade kit (40 blades only)
EF100.00.145Y FLS145 'Y' blade kit (48 blades only)

Parts

EF100.00.102B Bully FLS Series hammer (each)
GB/T11544 FLS Series belt (each)