

SFM-M Series Mulcher



The European designed BULLY SFM-M Series Mulcher is specifically designed for tractors 30 to 70hp.

The rear of the deck has a series of removable, height adjustable mulching rakes that hold large prunings (up to Ø 50mm) in the cutting chamber for maximum mulching. This results in a high-quality cut in vineyards, orchards and pastures.

The fixed, bolt-on tower has three mounting positions, 150mm apart, to enable the operator to offset the mulcher.



Code	TFSM130M	TFSM145M	TFSM160M
Size reference	1.3m 4'3" 51"	1.45m 4'9" 57"	1.6m 5'4" 64"
Side transmission	Belt drive		
Belts	Three (3) BX type	Four (4) BX type	
Gearbox	70hp, 540rpm with freewheel		
PTO shaft/clutch	Series 4		
Skids	Adjustable, three (3) positions		
Rear roller	Ø 140mm, height adjustable		
Finish	Powder coated		
Rotor swing dia. (mm)	380		
Rotor diameter (mm)	160		
Rotor speed (rpm)	2083		
Type of blade	Hammer standard 'Y' blades on request		
No. of hammers	16	18	20
Tower position/offset	Fixed/bolt-on tower with three (3) mounting positions, 150mm apart		
Linkage	Category 1		
Guarding	Standard with CE compliant, individual metal flap guarding		
Overall width (mm)	1450	1620	1770
Working width (mm)	1300	1450	1600
Cutting height (mm)	20 - 105		
Tractor range (hp)	30 - 70	35 - 70	40 - 70
Weight (kg)	366	388	412

Parts

17295 Bully SFM Series hammer (each)
 17228 Bully SFM Series Y blade (each)
 17229 Bully SFM Series Y blade spacer (each)

Parts

17699 SFM130-M belt set (3 belts)
 17698 SFM Series belt set (4 belts)