

S Range Rotary Cutter



KANGA S Range Rotary Cutters are general purpose implements designed for tough Australian conditions.

The hot dipped galvanized 3mm deck is fully reinforced underneath, creating a clean top design that reduces the collection of debris and water. Front and rear incorporated safety chains come standard, for maximum safety.

The lowered high tensile cutter bar allows a higher volume of material to be easily discharged producing fast, clean, dependable cutting in light scrub, regrowth and long grass.




Code	KSSR120	KSSR135	KSSR150
Size reference	1.2m 4'0" 48"	1.35m 4'6" 54"	1.5m 5'0" 60"
Construction	3mm, round-back, clean top deck with reinforced subframe		
Gearbox	40hp, 540rpm, 1:1.93 ratio		
PTO shaft/clutch	Series 4 with 150mm (6") friction (slip) clutch		
Skids	Adjustable, positive locking, four (4) positions (30mm increments)		
Cutter bar	Lowered, bolt together, high tensile steel		
Blades	Stepped, suction, heat-treated, spring steel pivoting on hardened bushes		
Linkage/Mounting	Double clevis, category 1 and 2		
Tower position(s)	Multiple - offset (left and right) and centre mounted		
Finish	Hot dipped galvanized deck and painted parts		
Stone guards	Front and rear chains incorporated into the deck		
Overall width (mm)	1410	1560	1710
Cutting width (mm)	1200	1350	1500
Cutting height (mm)	50 - 140		
Tractor range (hp)	28 - 40	35 - 50	40 - 50
Blade tip speed (ft/min)	13,119	14,760	16,400
Weight (kg)	250	280	300

Options
KSRDW KANGA light-duty depth wheel

Parts
100.134 KANGA stepped suction blades (pair)
100.135 KANGA 3/4" blade bolt kit
100.136 KANGA 7/8" blade bolt kit (suit cutters pre-2008)



Multi mount sliding tower



Blade bolt inspection cap



Blade exclusion zones



Waterproof manual holder



Countersunk blade bolts



Depth wheel (optional)