

PX1153 SERIES



THE NEXT STEP FORWARD.

The Kioti PX1153 cab tractor is a high-performance agricultural machine designed for demanding tasks and optimal operator comfort.

Equipped with a powerful 110-horsepower diesel engine, the PX1153 delivers robust performance and efficiency, making it ideal for heavy-duty farming operations. Its advanced transmission system ensures smooth and precise control, while the hydraulic system provides exceptional lifting capacity and implement compatibility. The spacious, climate-controlled cab is designed with the operator in mind, featuring ergonomic controls, an adjustable seat, and excellent visibility for reduced fatigue and increased productivity.

The PX1153 also includes modern technological features such as a digital dashboard, easy-to-access maintenance points, and comprehensive safety mechanisms. Whether plowing, planting, or harvesting, the Kioti PX1153 cab tractor offers reliable power, comfort, and efficiency for professional farmers and agricultural enterprises.






PX1153 CAB









PX1153 CAB

ENGINE

- Perkins 1104D-44TAG
- Liquid Cooled 4 Cylinder Diesel Turbo
- 4399cc Displacement
- 115 HP @ 2400 rpm
- 120 Litre Fuel Tank Capacity
- Dual Air Cleaner

TRANSMISSION

- Synchro Mesh
- Power Shuttle
- Push Button Hand Clutch
- Wet Multi Disc Clutch
- 32F x 32R Speed with Hydraulic High/Low
- Rear Differential Lock

HYDRAULICS & LINKAGE

- Main Pump Capacity 74.8lpm
- Steering Pump Capacity 46.5lpm
- Total Maximum Flow 121.3lpm
- 3630kg Maximum Rear Linkage Lift Capacity
- Power Steering
- Category 2 Three Point Linkage
- Position, Draft, ELC Mixed Control Lift System
- 4 Rear Remote Outlets
- Clevis Type Rear Draw Bar

POWER TAKE OFF

- Independent 540 / 1000 rpm PTO
- Auto PTO

BRAKES

Wet Multi Disc Type

OPERATOR ENVIRONMENT

- High Quality Fully Adjustable Air Suspension Seat with Armrests and Backrest
- Adjustable Steering Wheel and Instruments
- Flat Operator Deck

CABIN

- Deluxe Cabin with A/C and Heating
- Radio
- Front and Rear Wipers
- Internal / External Air Exchanger Filters
- 12v Refrigerator

TRAVEL SPEEDS

- Forward 0.65 39.64 kph
- Reverse 0.65 39.37 kph

DIMENSIONS

Overall Length (inc 3PL) 4120mm

Overall Height 2750mm

Overall Width (min Tread) 2293mm

Wheelbase 2305mm

Ground Clearance (Min)
475mm

Weight 3702kg

TYRES
AG Radial Tyres Front
440 / 65R24

AG Radial Tyres Rear 540 / 65R34





*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

BALE SPIKE